



## Eco8 Tower Light

### PORTABLE SOLAR LIGHTING TOWER

**200h**

**200h Running Time**



**HVO Fuel**



**4,200sqm Area  
Illuminated**



Our Eco8 units come with 6 multi-directional 160W, 48V LED lights offering an illumination area of 4,200sqm and a running time of up to 200 hours. – maximising safety, good value, uptime and efficiency while minimising costs, pollutants and CO2 emissions.

## Features & Benefits

- Multi-directional adjustable and tiltable floodlights.
- 6 x 160W, 48V LED lights.
- 7 sections hydraulic vertical tower 8.5 m, 340° rotatable.
- Galvanized metalworks.
- Very compact dimensions for easy handling & transportability, up to 13 units per truck.
- Central lifting eye, longitudinal and transversal forklift pockets for effective handling.
- Control panel alarms for engine protection and fuel level indicator.
- Circuit breaker for electrical protection against overload.
- External emergency stop button.
- Fully bunded tank, 110%
- Certified wind stability up to 110km/h.
- 4 height adjustable stabilizers.
- On board levels for guidance during stabilization.
- Amoss safety brake.

# Specifications

## DIMENSIONS

MINIMUM	2540 X 1390 X 2420 mm (L x W x H)
MAXIMUM	2540 X 1550 X 8500 mm (L x W x H)
WEIGHT	920 kg

## FLOODLIGHTS

TYPE	LED
POWER (EACH)	160 W
FLOODLIGHTS NUMBER	6
OPTIONS	Timer
ILLUMINATED AREA	4,200 sqm

## MAST

LIFTING METHOD	Hydraulic
MAX. HEIGHT	8.5 m
MAX WIND SPEED	110 km/h
ROTATION	340°

## ENGINE

MODEL	Kubota Z482*
FUEL	Diesel
R.P.M.	1500
TANK CAPACITY	110 L
CONSUMPTION	0.55 L/h
RUNNING TIME	200 h
NOISE LEVEL AT 7M	65 dBA

