



## LEDPROSLB

### DEDICATED PIR DETECTOR FOR LEDPRO FLOODLIGHTS - BLACK

- Dedicated PIR for use with Timeguard LEDPRO floodlights
- 2x cable entries suitable for PG11 gland (glands not supplied)
- Fits ALL Timeguard LEDPRO floodlights
- Simply replaces the terminal cover and plugs in to the LEDPRO floodlight - no extra cabling necessary
- Installer friendly captive terminal cover screws
- Tilt and rotate adjustable head for accurate reliable detection
- Photocell sensor (Adjustable) and manual override function complete with masking kit

### Technical Data

Operating Voltage	230V AC
Frequency	50Hz
Installation Type	Plug-in (LEDPRO Module)
Earth Class Rating	Class I
Ingress Protection Rating	IP55
Setting Type	Dial
Approved Mounting Height (m)	2.5
Motion Detection (m)	12
Detection Angle	180°
Pan & Tilt Adjustment	Pan Left 90°, Pan Right 90°, Tilt Down 150°
Standby Consumption	<1W
Switch Rating	250W LED, 1000W Halogen, 200W CFL, 500W Fluorescent Tube w/o PF Correction
ON Time Adjustment	3 Seconds to 18 Minutes
Lux Level	2 to 1000

Detection Range (M)	12
Permanent ON Facility	Yes (Pulse Override)
Multiple Unit Support	Yes
Cable Entry(s)	Back Entry

## General

Weight (g)	124
Height (mm)	114
Width (mm)	78
Depth (mm)	108
Body Construction	Polycarbonate
Product Colour	Black
EAN Number	5012483013779
Guarantee Period	3 Years
Trade Tariff Commodity Code	8536508090

